



SKID TANKS

NON U/L HTC STANDARD SINGLE WALL ABOVE-GROUND STORAGE TANKS (AST)

HALL TANK

STANDARD FEATURES

- Capacities range from 120 to 1,000 Gallons
- 3 - 2" FNPT Tank Flanges on top
- 1 - 1" FNPT Tank Flange w/ Plug in bottom (Drain)
(1-1/2" in 1,000 gallon tanks)
- 1 - Lifting hook (72" lengths & Below)
- 2 - Lifting hooks (Lengths over 72")
- 1 - Angle Iron Skid Assembly w/ Pull Bar
- Exterior is primed & finish painted gray



OPTIONS

- Custom Diameter & Length to fit Customer Needs
- Single Bulkhead
- Double Bulkhead w/ 2" Tank Flange test fitting
- 2" Fill Cap
- 2" MNPT Plug
- 1/4" to 4" FNPT Tank Flange openings
- Kruger At-A-Glance Gauge
- 1/2" Site Gauge Assembly
- Banded Construction for mobile transportation
- Internal Baffles for mobile transportation
- Pump Platform
- Reel Mount Bracket
- Exterior is Sandblasted & coated to customer specified color

CAPACITY	DIAMETER	LENGTH	THICKNESS	WEIGHT
150 GALLON	30"	48"	12 GAUGE	304 LBS
280 GALLON	36.5"	60"	12 GAUGE	418 LBS
300 GALLON	36.5"	66"	12 GAUGE	444 LBS
330 GALLON	36.5"	72"	12 GAUGE	470 LBS
550 GALLON	42"	93.5"	12 GAUGE	633 LBS
1000 GALLON	45.5"	144"	12 GAUGE	1000 LBS
1000 GALLON	45.5"	144"	10 GAUGE	1216 LBS
2000 GALLON	64"	144"	10 GAUGE	1675 LBS